





inventronics

Profiles & Accessories

INDEX

2 SURFACE MOUNTED PROFILES

- 4 Products Overview
- 6 Surface slim profile 15x6 mm
- 7 Surface slim profile 16x12 mm
- 8 Minimal surface slim profile 15x10 mm
- 9 Optical surface slim profile 16x12 mm
- 10 Surface wide profile 26x10 mm
- 11 Surface wide profile 26x25 mm

14 RECESSED PROFILES

- 16 Products Overview
- 17 Recessed slim profile 15x6 mm
- 18 Recessed slim profile 16x12 mm
- 19 Recessed wide profile 26x25 mm

22 SPECIAL PROFILES

- 24 Products Overview
- 26 Corner surface slim profile 19x19 mm
- 27 Corner surface wide profile 46x27 mm
- 28 Pendant wide profile 56x70 mm
- 29 Wall profile 25x110 mm

32 LIGHT DISTRIBUTION CURVES


36 SYSTEM UNIFORMITY MATCHING TABLE

38 FLEX SUMMARY



SURFACE MOUNTED PROFILES





Surface slim
profile 15x6 mm

Surface slim
profile 16x12 mm

Minimal surface
slim profile 15x10 mm

SURFACE MOUNTED PROFILES




Optical surface slim
profile 16x12 mm

Surface wide
profile 26x10 mm

Surface wide
profile 26x25 mm








SURFACE MOUNTED PROFILES


Surface slim profile 15x6 mm



EAN10	Product Name	Box Composition	L	W	H
6937186130860	1 QMS Aluminium Profile 3m TU15H6 G2	1 pc	3000 mm	16 mm	6 mm
6937186148469	2 QMS Cover Flat Opal PC 3m G1	1 pc	3000 mm	13 mm	4 mm
6937186131744	3 QMS Cover Flat Transparent PC 3m G2	1 pc	3000 mm	13 mm	4 mm
6937186130846	4 QMS End Caps Square Grey ABS TU15H6 G2	40 pcs	9 mm	15 mm	6 mm
6937186130822	5 QMS End Caps Square Grey with hole ABS TU15H6 G2	40 pcs	9 mm	15 mm	6 mm
6937186148483	6 QMS Mounting Brackets Stainless Steel G1	40 pcs	20 mm	17 mm	10 mm
6937186146168	7 QMS Slim Adjustable Brackets Grey ASA G1	40 pcs	20 mm	22 mm	19 mm



ACCESSORIES



2




3




4



5



6



7




SURFACE MOUNTED PROFILES

Surface slim profile 16x12 mm



EAN10	Product Name	Box Composition	L	W	H
6937186126740	1 QMS Aluminium Profile 3m TU16H12 G2	1 pc	3000 mm	16 mm	12 mm
6937186148469	2 QMS Cover Flat Opal PC 3m G1	1 pc	3000 mm	13 mm	4 mm
6937186131744	3 QMS Cover Flat Transparent PC 3m G2	1 pc	3000 mm	13 mm	4 mm
6937186126764	4 QMS End Caps Square Grey ABS TU16H12 G2	40 pcs	10 mm	16 mm	12 mm
6937186126788	5 QMS End Caps Square Grey with hole ABS TU16H12 G2	40 pcs	10 mm	16 mm	12 mm
6937186148483	6 QMS Mounting Brackets Stainless Steel G1	40 pcs	20 mm	17 mm	10 mm
6937186146168	7 QMS Slim Adjustable Brackets Grey ASA G1	40 pcs	20 mm	22 mm	19 mm




ACCESSORIES





SURFACE MOUNTED PROFILES

Minimal surface slim profile 15x10 mm



EAN10	Product Name	Box Composition	L	W	H
6937186141200	1 LTS Aluminium Profile 2m Slimtrack G1	5 pcs	2000 mm	15 mm	10 mm
6937186148742	2 LTS Cover Flat Transparent PC 2m G1	5 pcs	2000 mm	18 mm	5 mm
6937186148803	3 LTS End Caps Flat Grey HDPE G1	20 pcs	7 mm	20 mm	13 mm
6937186148728	4 LTS Cover Flat High Opal PC 2m G1	5 pcs	2000 mm	18 mm	10 mm
6937186148780	5 LTS End Caps Flat High Grey HDPE G1	20 pcs	7 mm	20 mm	18 mm
6937186148841	6 LTS Cover Round Opal PC 2m G1	5 pcs	2000 mm	18 mm	24 mm
6937186148827	7 LTS Mounting Brackets Grey HDPE G1	20 pcs	34 mm	18 mm	10 mm

ACCESSORIES






SURFACE MOUNTED PROFILES

Optical surface slim profile 16x12 mm



EAN10	Product Name	Box Composition	L	W	H
6937186148421	1 QMS Aluminium Profile 3m TU16H12LS G1	1 pc	3000 mm	16 mm	12 mm
6937186148667	2 QMS Cover Optical Round Transparent PC 3m G1	1 pc	3000 mm	15 mm	10 mm
6937186148544	3 QMS End Caps Square Grey ABS TU16H12LS G1	40 pcs	10 mm	16 mm	18 mm
6937186148681	4 QMS End Caps Square Grey with hole ABS TU16H12LS G1	40 pcs	10 mm	16 mm	18 mm
6937186148483	5 QMS Mounting Brackets Stainless Steel G1	40 pcs	20 mm	17 mm	10 mm
6937186146168	6 QMS Slim Adjustable Brackets Grey ASA G1	40 pcs	20 mm	22 mm	19 mm



ACCESSORIES






SURFACE MOUNTED PROFILES


Surface wide profile 26x10 mm



EAN10	Product Name	Box Composition	L	W	H
6937186126849	1 QMW Aluminium Profile 2m TU26H10 G2	5 pcs	2000 mm	26 mm	10 mm
6937186126887	2 QMW Cover Round Frosted PC 2m G2	5 pcs	2000 mm	26 mm	19 mm
6937186126900	3 QMW End Caps Square Grey HDPE TU26H10 G2	20 pcs	10 mm	26 mm	25 mm
6937186126962	4 QMW Mounting Brackets Grey ABS G2	20 pcs	39 mm	29 mm	10 mm
6937186126986	5 QMW Adjustable Brackets Grey ABS G2	20 pcs	21 mm	29 mm	15 mm
6937186127006	6 QMW Stainless Steel Springs G2	20 pcs	10 mm	60 mm	34 mm



ACCESSORIES






SURFACE MOUNTED PROFILES

Surface wide profile 26x25 mm



EAN10	Product Name	Box Composition	L	W	H
6937186126825	1 QMW Aluminium Profile 2m TU26H25 G2	5 pcs	2000 mm	26 mm	25 mm
6937186126887	2 QMW Cover Round Frosted PC 2m G2	5 pcs	2000 mm	26 mm	19 mm
6937186126948	3 QMW End Caps Round Grey HDPE TU26H25 G2	20 pcs	10 mm	26 mm	40 mm
6937186126863	4 QMW Cover Flat Frosted PC 2m G2	5 pcs	2000 mm	26 mm	5 mm
6937186126924	5 QMW End Caps Square Grey HDPE TU26H25 G2	20 pcs	10 mm	26 mm	26 mm
6937186126962	6 QMW Mounting Brackets Grey ABS G2	20 pcs	39 mm	29 mm	10 mm
6937186126986	7 QMW Adjustable Brackets Grey ABS G2	20 pcs	21 mm	29 mm	15 mm
6937186127006	8 QMW Stainless Steel Springs G2	20 pcs	10 mm	60 mm	34 mm



ACCESSORIES



PRODUCT'S COMPONENTS

LTS | Mounting Brackets
Grey PP | G1



Minimal surface slim profile
15x10 mm



LTS | End Caps Flat High
Grey HDPE | G1



Strip LED



LTS | Cover Flat High
Opal PC 2m | G1



HIMMLISCHES THEATER MUSEUM

LOCATION

Stift Neuzelle, Germany



LIGHTING DESIGN

Konzeptlicht lighting solutions GmbH



RECESSED PROFILES





Recessed slim
profile 15x6 mm

Recessed slim
profile 16x12 mm

Recessed wide
profile 26x25 mm

RECESSED PROFILES




RECESSED PROFILES

Recessed slim profile 15x6 mm



EAN10	Product Name	Box Composition	L	W	H
6937186126702	1 QMS Aluminium Profile 3m TU15H6W3 G2	1 pc	3000 mm	22 mm	6 mm
6937186148469	2 QMS Cover Flat Frosted PC 3m G1	1 pc	3000 mm	13 mm	4 mm
6937186131744	3 QMS Cover Flat Transparent PC 3m G2	1 pc	3000 mm	13 mm	4 mm
6937186130921	4 QMS End Caps Square Grey ABS TU15H6W3 G2	40 pcs	22 mm	22 mm	6 mm
6937186126726	5 QMS End Caps Square Grey with hole ABS TU15H6W3 G2	40 pcs	22 mm	22 mm	6 mm



ACCESSORIES






RECESSED PROFILES

Recessed slim profile 16x12 mm




EAN10	Product Name	Box Composition	L	W	H
6937186146229	1 QMS Aluminium Profile 3m TU16H12W3 G1	1 pc	3000 mm	22 mm	12 mm
6937186148469	2 QMS Cover Flat Opal PC 3m G1	1 pc	3000 mm	13 mm	4 mm
6937186131744	3 QMS Cover Flat Transparent PC 3m G2	1 pc	3000 mm	13 mm	4 mm
6937186130907	4 QMS End Caps Square Grey ABS TU16H12W3 G2	40 pcs	22 mm	22 mm	12 mm
6937186130884	5 QMS End Caps Square Grey with hole ABS TU16H12W3 G2	40 pcs	22 mm	22 mm	12 mm




ACCESSORIES






RECESSED PROFILES

Recessed wide profile 26x25 mm



EAN10	Product Name	Box Composition	L	W	H
6937186126801	1 QMW Aluminium Profile 2m TU26H25W10 G2	5 pcs	2000 mm	44 mm	26 mm
6937186126887	2 QMW Cover Round Frosted PC 2m G2	5 pcs	2000 mm	26 mm	19 mm
6937186126948	3 QMW End Caps Round Grey HDPE TU26H25 G2	20 pcs	10 mm	26 mm	40 mm
6937186126863	4 QMW Cover Flat Frosted PC 2m G2	5 pcs	2000 mm	26 mm	5 mm
6937186126924	5 QMW End Caps Square Grey HDPE TU26H25 G2	20 pcs	10 mm	26 mm	26 mm
6937186126962	6 QMW Mounting Brackets Grey ABS G2	20 pcs	39 mm	29 mm	10 mm
6937186126986	7 QMW Adjustable Brackets Grey ABS G2	20 pcs	21 mm	29 mm	15 mm
6937186127020	8 QMW Stainless Steel Springs G2	20 pcs	15 mm	51 mm	39 mm

ACCESSORIES



2




3




4



5



6




7



8

PRODUCT'S COMPONENTS



NAMMOS RESTAURANT

LOCATION


Dubai


LIGHTING DESIGN


Huda Lighting & Elastic Architects



SPECIAL PROFILES








Corner surface wide
profile 46x27 mm

Pendant wide
profile 56x70

**SPECIAL
PROFILES**

A 3D architectural rendering of a corner surface slim profile and a wall profile. The corner profile is a thin, dark grey L-shaped extrusion. The wall profile is a larger, white extrusion. Both are shown in a perspective view, with the corner profile running diagonally across the frame. The wall profile is shown as a vertical section on the right side. The background is a light grey wall and floor.

Corner surface slim
profile 19x19 mm

Wall profile 25x110




SPECIAL PROFILES


Corner surface slim profile 19x19 mm




EAN10	Product Name	Box Composition	L	W	H
6937186131706	1 QMS Aluminium Profile 3 m T45D19H19 G2	1 pc	3000 mm	19 mm	19 mm
6937186148469	2 QMS Cover Flat Opal PC 3 m G1	1 pc	3000 mm	13 mm	4 mm
6937186131744	3 QMS Cover Flat Transparent PC 3 m G2	1 pc	3000 mm	13 mm	4 mm
6937186131720	4 QMS End Caps Grey ABS T45D19H19 G2	40 pcs	22 mm	19 mm	19 mm
6937186133632	5 QMS End Caps Grey with hole ABS T45D19H19 G2	40 pcs	22 mm	19 mm	19 mm
6937186148506	6 QMS T45 Mounting Brackets Stainless Steel G1	40 pcs	20 mm	20 mm	10 mm



ACCESSORIES



2




3




4



5




6




SPECIAL PROFILES

Corner surface wide profile 46x27 mm




EAN10	Product Name	Box Composition	L	W	H
6937186148407	1 QMW Aluminium Profile 3 m & 14 pcs of clips TK30D46H27 G1	1 pc	3000 mm	46 mm	27 mm
6937186148445	2 QMW Cover Round Frosted PC 3 m G1	1 pc	3000 mm	24 mm	20 mm
6937186148605	3 QMW Cover Flat Frosted PC 3 m G1	1 pc	3000 mm	22 mm	4 mm
6937186148582	4 QMW End Caps Left Grey ABS TK30D46H27 G1	40 pcs	8 mm	46 mm	27 mm
6937186148568	5 QMW End Caps Right Grey ABS TK30D46H27 G1	40 pcs	8 mm	46 mm	27 mm
6937186148629	6 QMW Clips for combining 2 parts ABS G1	40 pcs	9 mm	6 mm	6 mm


ACCESSORIES




2



3




4



5




6



SPECIAL PROFILES

Pendant wide profile 56x70 mm



EAN10	Product Name	Box Composition	L	W	H
6977078997805	1 FX-QMP-G1-TU56H70-BK-010QMP Aluminium profile 1 m TU56H70 G1 Black	1 pc	1000 mm	56 mm	70 mm
6977078997836	2 FX-QMP-G1-TU56H70-BK-015QMP Aluminium profile 1,5 m TU56H70 G1 Black	1 pc	1500 mm	56 mm	70 mm
6977078997867	3 FX-QMP-G1-TU56H70-BK-020QMP Aluminium profile 2 m TU56H70 G1 Black	1 pc	2000 mm	56 mm	70 mm
6977078997898	1 FX-QMP-G1-TU56H70-WH-010QMP Aluminium profile 1m TU56H70 G1 White	1 pc	1000 mm	56 mm	70 mm
6977078997928	2 FX-QMP-G1-TU56H70-WH-015QMP Aluminium profile 1,5 m TU56H70 G1 White	1 pc	1500 mm	56 mm	70 mm
6977078997959	3 FX-QMP-G1-TU56H70-WH-020QMP Aluminium profile 2 m TU56H70 G1 White	1 pc	2000 mm	56 mm	70 mm
6977078998192	4 FX-QMP-G1-CFDP-TU56H70-010QMP Cover Flat Frosted PC 1 m G1	1 pc	1000 mm	49 mm	2 mm
6977078998222	5 FX-QMP-G1-CFDP-TU56H70-020QMP Cover Flat Frosted PC 2m G1	1 pc	2000 mm	49 mm	2 mm
6977078998253	6 FX-QMP-G1-CFMP-TU56H70-010QMP Cover Flat Microprismatic PC 1 m G1	1 pc	1000 mm	49 mm	2 mm
6977078998284	7 FX-QMP-G1-CFMP-TU56H70-020QMP Cover Flat Microprismatic PC 2 m G1	1 pc	2000 mm	49 mm	2 mm

ACCESSORIES



2




2



4




6




SPECIAL PROFILES

Wall profile 25x110 mm




EAN10	Product Name	Box Composition	L	W	H
6977078998017	1 FX-QMR-G1-TT25H110-BK-005QMR Aluminium profile 0,5 m TT25H110 G1 Black	1 pc	500 mm	22 mm	110 mm
6977078998048	2 FX-QMR-G1-TT25H110-BK-010QMR Aluminium profile 1 m TT25H110 G1 Black	1 pc	1000 mm	22 mm	110 mm
6977078998079	3 FX-QMR-G1-TT25H110-BK-015QMR Aluminium profile 1,5 m TT25H110 G1 Black	1 pc	1500 mm	22 mm	110 mm
6977078998109	1 FX-QMR-G1-TT25H110-WH-005QMR Aluminium profile 0,5 m TT25H110 G1 White	1 pc	500 mm	22 mm	110 mm
6977078998130	2 FX-QMR-G1-TT25H110-WH-010QMR Aluminium profile 1m TT25H110 G1 White	1 pc	1000 mm	22 mm	110 mm
6977078998161	3 FX-QMR-G1-TT25H110-WH-015QMR Aluminium profile 1,5 m TT25H110 G1 White	1 pc	1500 mm	22 mm	110 mm

ACCESSORIES




2



2

PRODUCT'S COMPONENTS










DIEZ ARENA FITNESS CENTER








LOCATION

Diez, Germany







LIGHT DISTRIBUTION CURVES







Profile	Cover	Optical Performance
Minimal surface slim profile 15x10 mm 	Flat Transparent 	-20%  
	Flat High Opal 	-35%  
	Round opal 	-40%  
Surface slim profile 15x6 mm 	Transparent 	-15%  
	Opal 	-40%  
Surface slim profile 16x12 mm 	Transparent 	-24%  
	Opal 	-45%  

Profile	Cover	Optical Performance
Optical surface slim profile 16x12 mm 	10° 	-30%  
	30° 	-30%  
	45° 	-30%  
	60° 	-30%  
	90° 	-30%  





LIGHT DISTRIBUTION CURVES



Profile	Cover	Optical Performance
Surface wide profile 26x10 mm 	Flat Frosted	-35%  
	Round Frosted	-30%   
Surface wide profile 26x25 mm 	Flat Frosted	-55%  
	Round Frosted	-50%   

LIGHT DISTRIBUTION CURVES

Profile	Cover	Optical Performance	
Recessed slim profile 15x6 mm 	Transparent	-15%	 
	Opal	-40%	 
Recessed slim profile 16x12 mm 	Transparent	-24%	 
	Opal	-45%	 
Recessed wide profile 26x25 mm 	Flat Frosted	-55%	 
	Round Frosted	-50%	 

LIGHT DISTRIBUTION CURVES

Profile	Cover	Optical Performance		
Corner surface slim profile 19x19 mm 	Transparent	-38%		
	Opal	-57%		
Corner surface wide profile 46x27 mm 	Round Frosted	-39%		
	Flat Frosted	-43%		
Wall profile 25x110 mm 		-70%		

Profile	Cover	Optical Performance	
Pendant wide profile 56x70 mm  Opal	-40%		
	Microplastic 	-26%	
Opal	-40%		
	Flat Frosted 	-32%	

SYSTEM UNIFORMITY MATCHING TABLE

3 levels of uniformity:

Level 1	Level 2	Level 3
		

			Indoor / Outdoor					
		LINEARlight FLEX	Infinite (80)	Uniformity (140)	Tunable White (160)	Monochrome (120)	RGB (50)	RGB(W) (60)
		TEC FLEX	Power (70)	Shortpitch (140)	Tunable White (160)		RGB (50)	RGB(W) (60)
SURFACE								
Minimal surface slim profile 15x10 mm	Flat Transparent	1 	1 	1 	1 	1 	1 	
	Flat Opal	2 	3 	3 	3 	2 	2 	
	Round opal	3 	3 	3 	3 	3 	3 	
Surface slim profile 15x6 mm	QMS Cover Flat Opal PC 3 m G1	2 	2 	2 	2 	2 	2 	
	QMS Cover Flat Transparent PC 3 m G2	1 	1 	1 	1 	1 	1 	
Surface slim profile 16x12 mm	QMS Cover Flat Opal PC 3 m G1	2 	3 	3 	3 	2 	2 	
	QMS Cover Flat Transparent PC 3 m G2	1 	1 	1 	1 	1 	1 	
Optical surface slim profile 12x16 mm	QMS Cover Optical Round Transparent PC 3 m G1	1 	1 	1 	1 	1 	1 	
Surface wide profile 26x10 mm	QMW Cover Round Frosted PC 2m G2	3 	3 	3 	3 	3 	3 	
Surface wide profile 26x25 mm	QMW Cover Round Frosted PC 2 m G2	3 	3 	3 	3 	3 	3 	
	QMW Cover Flat Frosted PC 2 m G2	3 	3 	3 	3 	3 	3 	

3 levels of uniformity:

Level 1	Level 2	Level 3
		

	Indoor / Outdoor					
LINEARlight FLEX	Infinite (80)	Uniformity (140)	Tunable White (160)	Monochrome (120)	RGB (50)	RGB(W) (60)
TEC FLEX	Power (70)	Shortpitch (140)	Tunable White (160)		RGB (50)	RGB(W) (60)

RECESSED							
Recessed slim profile 15x6mm	QMS Cover Flat Frosted PC 3 m G1	2 	3 	3 	3 	2 	2 
	QMS Cover Flat Transparent PC 3 m G2	1 	1 	1 	1 	1 	1 
Recessed slim profile 16x12mm	QMS Cover Flat Opal PU 3 m G1	2 	3 	3 	3 	2 	2 
	QMS Cover Flat Transparent PU 3 m G2	1 	1 	1 	1 	1 	1 
Recessed wide profile 26x25mm	QMW Cover Round Frosted PU 2 m G2	3 	3 	3 	3 	3 	3 

	Indoor / Outdoor					
LINEARlight FLEX	Infinite (80)	Uniformity (140)	Tunable White (160)	Monochrome (120)	RGB (50)	RGB(W) (60)
TEC FLEX	Power (70)	Shortpitch (140)	Tunable White (160)		RGB (50)	RGB(W) (60)

SPECIAL							
Corner surface slim profile 19x19 mm	QMS Cover Flat Opal PU 3 m G1	2 	3 	3 	3 	2 	2 
	QMS Cover Flat Transparent PU 3 m G1	1 	1 	1 	1 	1 	1 
Corner surface wide profile 46x27 mm	QMW Cover Round Frosted PU 2 m G2	3 	3 	3 	3 	3 	3 
	QMW Cover Flat Frosted PU 2 m G2	2 	2 	2 	2 	2 	2 
Pendant wide profile 56x70 mm	QMP Cover Flat Frosted PU 1 m G1	3 	3 	3 	3 	3 	3 
	QMP Cover Flat Microprismatic PU 1 m G1	3 	3 	3 	3 	3 	3 
Wall profile 25x110 mm	Cover	2 	3 	3 	3 	2 	2 

FLEX SUMMARY

LINEARlight FLEX


		Max Length	LEDs/m	FLUX	CCTs	CRIs	IP	Efficiency	Step Mac Adam	Input	Made in Italy	Warranty	Lifetime	Certifications
Infinite		Up to 18m	80 LEDs/m	From 500 to 4000 lm/m	2400K 2700K 3000K 4000K Other CCTs upon request	80+ 90+	IP00 IP68	Up to 167 lm/W	<2	24 & 48V	✓	7	L80B10 @60kh	CE, UKCA, ENEC, VDE, CrUS
Uniformity		Up to 10m	140 LEDs/m	From 800 to 2000 lm/m	2400K 2700K 3000K 4000K Other CCTs upon request	80+ 90+ 95+	IP00 IP68	Up to 140 lm/W	<2	24V	✓	7	L80B10 @60kh	CE, UKCA, ENEC, VDE, CrUS
Tunable White		Up to 5m	167 LEDs/m	From 1100 to 3400 lm/m	2700-5700K 2500-4000K	90+	IP00 IP68	-	<2	24V	✓	7	L80B10 @60kh	CE, UKCA, ENEC, VDE, CrUS
RGB(W)		Up to 5m	60 LEDs/m	From 600 to 1300 lm/m	2200K / 2700K / 3000K / 4000K / 6500K (on white)	80+ 90+ (on white)	IP00 IP68	-	<3	24V	✓	7	L80B10 @60kh	CE, UKCA, ENEC, VDE, CrUS
Monochrome		Up to 10m	60 LEDs/m	240 (red) / 640 (blue) / 130 (green) lm/m	-	-	IP00 IP68	-	<3	24V	✓	7	L80B10 @60kh	CE, UKCA, ENEC, VDE, CrUS

FLEX SUMMARY


TEC FLEX

		Max Length	LEDs/m	FLUX	CCTs	CRIs	IP	Efficiency	Step Mac Adam	Input	Made in Italy	Warranty	Lifetime	Certifications
Power		Up to 5m	70 LEDs/m	From 600 to 2000 lm/m	2700K 3000K 4000K	80+ 90+	IP00 IP66	Up to 144 lm/W	<3	24 & 48V	✓	5	L70B50 @50kh	CE, UKCA, ENEC
Shortpitch		Up to 5m	140 LEDs/m	From 600 to 2000 lm/m	2400K 2700K 3000K 4000K	80+ 90+	IP00 IP67	Up to 136 lm/W	<3	24V & 48V	✓	5	L70B50 @50kh	CE, UKCA, ENEC
Tunable White		Up to 5m	140 LEDs/m	1820 lm/m	2700-6500K	80+	IP00 IP67	-	<3	24V	×	5	L70B50 @50kh	CE, UKCA, ENEC
RGB		Up to 5m	Up to 120 LEDs/m	-	3000K (on white)	80+ (on white)	IP00 IP67	-	<3	24V	×	5	L70B50 @50kh	CE, UKCA, ENEC


ICONS




Surface Application




Recessed Application




Corner Surface Application



Only for indoor installation




Indoor and outdoor installation *



Customizable kit upon request

CERTIFICATIONS AND NOTES



CE



UKCA



Made in Europe



RoHS

* Notes:


All profiles and their accessories, present in the document, are compatible with the use of our CV modules (see match table) as they do not alternate their specifications.

All profiles and accessories are tested in their mechanical functionality, therefore, it is allowed to use the accessory in the specified application (excluding situations where the installer will not follow the installation instructions).


On an aesthetic level, we inform that, depending on the material, profiles and accessories may undergo aesthetic alterations depending on the environment in which they will be installed.

The profiles are compatible with outdoor installations (where specified) in their mechanical and functional parts.

Accessory covers contain UV protection (however, this does not exclude cases of long-term yellowing of the material).

A thick orange line that starts from the left edge of the frame, extends diagonally upwards and to the right, and then curves into a smooth, rounded shape pointing towards the center.

Building a brighter future

A thick orange line that starts from the right edge of the frame, extends diagonally downwards and to the left, and then curves into a smooth, rounded shape pointing towards the center.

Service contact:

Inventronics GmbH
Parkring 31-33,
85748 Garching,
Germany

www.inventronicsglobal.com/ds
support@inventronicsglobal.com

inventronics